

Continuous Ice Cream Freezer



Salient Features

- ④ Stainless steel 304 frame and covering panels.
- ④ Hard chrome plated cylinder.
- ④ Solid dasher or open dasher with eccentric shaft.
- ④ Digital ammeter and voltmeter.
- ④ Hour meter
- ④ Anti freeze protection device
- ④ Speed variable device with indicator
- ④ S. S. diaphragm pressure gauge
- ④ Suction and discharge pressure gauges for refrigerant circuit.
- ④ Hot gas supply to freezing cylinder
- ④ Interlock & safety-controls .



Technical Specification

Model	CF-150	CF-200	CF-300	CF-400
Capacity ,l/hr	150	200	300	400
Dasher motor, kW	1.5	1.5	3.75	3.75
Mix pump, kW	0.75	0.75	1.1	1.1
Compressor, kW	HERMETIC	HERMETIC	HERMETIC	HERMETIC
Refrigerant	R-22	R-404a	R-22	R-404a
Water flow rate at 30°C, l/hr	1500	2000	3500	4500
Dimension LxWxD	1250x675x1030	1250x675x1030	1308x900x1350	1308x900x1350

Exported by:

ENCON Consulting Engineers
M-28, 7th Floor, Marigold,
Krishnakeval Township,
Kondhwa Khurd,
Pune 411048-INDIA.

Tel/Fax: +91 20 26831210 Cell Phone: +91 94 22 00 2758
 Email: encon@vsnl.com / enconengineer@yahoo.co.in



TWIN VOLUMETRIC FILLER

Salient Features

- ④ TWIN NOZZLES WITH ADJUSTABLE ELECTRONIC TIMER
- ④ SUITABLE TO ATTACH FLOWER SHAPE NOZZLES
- ④ UP-DOWN MOTION FOR NOZZLE
- ④ S.S. 304 SELF SUPPORTING STAND AND CONTROL PANEL
- ④ ALL CONTACT PART OF S.S. 304 OR FOOD GRADE MATERIAL
- ④ COMPLETE WITH PNEUMATIC CYLINDER AND ACCESSORIES
- ④ SUITABLE TO FILL TWO DIFFERENT FLAVOR IN A CUP



Technical Specification

Model	VF-2
Capacity cup/hr	2000-3000
Volume ml	50-150
Air, m ³ /hr, fad	2.5 with 6 bar pressure
Length, mm	600
Width, mm	400
Height, mm	1600

Exported by:

ENCON Consulting Engineers
M-28, 7th Floor, Marigold,
Krishnakeval Township,
Kondhwa Khurd,
Pune 411048-INDIA.

Tel/Fax: +91 20 26831210 Cell Phone: +91 94 22 00 2758

Email: encon@vsnl.com / enconengineer@yahoo.co.in



HOMOGENIZER

Salient Features

- ④ Pressure adjustment by hand wheel.
- ④ Two stage homogenization
- ④ S. S. diaphragm type sanitary design pressure gauge.
- ④ High strength steel eccentric shaft and connecting rod assembly.
- ④ Splash lubricating system
- ④ All product contact parts of S.S. 304



Technical Specification			
Model	HM-150	HM-300	HM-500
Capacity, l/hr.	150	300	500
Motor, Kw	1.88	2.25	5.63
Max. working pressure, bar	170	170	170
No. of pistons	3	3	3
Length, mm	700	700	700
Width, mm	630	630	630
Height, mm	800	800	800

Exported by:

ENCON Consulting Engineers
M-28, 7th Floor, Marigold,
Krishnakeval Township,
Kondhwa Khurd,
Pune 411048-INDIA.

Tel/Fax: +91 20 26831210 Cell Phone: +91 94 22 00 2758
Email: encon@vsnl.com / enconengineer@yahoo.co.in

